



WALLCOVERING

Vu patterns meet or exceed Type I requirements of CCC-W-408D and W-101.

PERFORMANCE SPECIFICATIONS

Weight (Avg):	15 oz (340 gr/m ²)
Backing:	Scrim
Installation:	Random Hang / Random Match
Roll Size:	52-54" (132/137 cm)

FIRE SAFETY

Class A – ASTM E84
NFPA 101 Life Safety Code
EN13501 (B-S1-d0)

ENVIRONMENTAL AND HEALTH

Phthalate Free
Health Product Declaration
Environmental Product Declaration
Meets State of Washington Building
Specification for Indoor Air Quality
Meets California Section 01350 Indoor Air Quality Standard
Aggressive manufacturing materials recovery and reuse program
Highly cleanable water-based inks
Free of PBDE's (Brominated Flame Retardants)

USGBC LEED SUPPORT

Supports USGBC LEED v4.1 Criteria
Materials and Resources; Building Product Disclosure and Optimization
(Construction Waste Management; HPD's)
Indoor Environmental Quality; Low emitting materials

MOISTURE, MOLD, AND MILDEW

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and the wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated. Further protection against mold growth may be achieved by microventing. Contact your supplier for additional information.

WARRANTY

Vu products are guaranteed to be free of defects in workmanship and material for five years.